



Mobile High pressure cleaner, oil-heated FH 1024 TCC

► Data Sheet

MADE IN GERMANY

1.0	Typee	FH 1024 TCC	
2.0	Capacity		
2.1	Mains connection	400 V 3 AC 50 Hz	
2.2	Nominal consumption	7.5 kW 15 A	
3.0	High pressure stage		
3.1	Working pressure	240 bar	
3.2	Water - volume flow	17 l/min	
3.3	Operating temperature	85 °C	
4.0	Steam stage		
4.1	Working pressure	30 bar	
4.2	Water - volume flow	9.5 l/min	
4.3	Operating temperature	140 °C	
4.4	Oil atomizing burner	Typee LB 03	
4.5	Burner capacity	80 kW	
4.6	without flame control		
4.7	Burner nozzle	Typee 2.00 / 45°	
4.8	Fuel oil EL - consumption 9.3 l/h at constant operation with maximum operating temperature		
4.9	Flue gas temperature	177 °C	
4.10	Flue gas mass flow temperature	137 kg/h	
4.11	Flue gas volume flow	173 m³/h related to a flue gas temperature of 177 °C	
5.0	Specification		
5.1	High pressure pump with 3 solid ceramic plungers 7041032000	Typee NP 16/15	Order nr.
5.2	Unloader safety valve	ULH for TCC	Order nr. 2098952000
5.3	protects the high pressure system		
5.4	with turning handle for the setting of the operating stages high pressure/steam		
5.5	Dosage of cleaning and preserving agents selectively adjustable		
5.6	Spray lance with hand screw connection		Order nr. 2096750000
5.7	with spray gun with hand screw union TCC 1		Order nr. 2095950000
5.8	with high pressure flat jet nozzle	Typee 2505	Order nr. 7023230000
5.9	with high pressure hose 10 m	Typee DN 8	Order nr. 2051560000
5.10	Electrical motor for high pressure pump drive	Capacity 5.5 kW	Order nr. 7040633000
5.11	Connecting cable 4 x 1.5 mm²	5 m with mains plug 16 A	
6.0	Dimensions with trolley (LxWxH)	1245x590x845 mm	
7.0	Weight	183 kg	



* EU declaration of conformity updated by the TÜV Hesse

subject to change without prior notice