



# Self-Service Wash Stations FOS 811 F - Liquid

## ► Data Sheet



<b>1.0</b>	<b>Type</b>	<b>FOS 811 F</b>
<b>2.0</b>	<b>Capacity</b>	
2.1	Mains connection	400 V 3 AC 50 Hz
2.2	Nominal consumption	5,0 kW
<b>3.0</b>	<b>High pressure stage</b>	
3.1	Operating pressure max.	110 bar
3.2	Water – Volume flow	11,5 l/min
3.3	Operating temperature max.	70 °C
<b>4.0</b>	<b>Steam stage</b>	
4.2	Volume flow max.	800 l/h
4.3	Operating temperature	140 °C
4.4	Heat capacity	51 kW
4.5	Fuel oil consumption at 60 °C	4,8/5,8 kg/h - l/h
<b>5.0</b>	<b>Specification</b>	
5.1	oil-heated, 4 programmes, frost protection circuit	
5.2	HP-hose 10 m, spray gun, spray lance	
5.3	without water softener	
5.4	without boom	
5.5	with liquid detergent tank	
5.6	with oil atomization burner including pre-heater and flame control	
5.7	fuel oil tank with fuel filler and level indicator	
5.8	with electrical coin checker for 4 different coins, e.g.: 50 Cent, 1 Euro, 2 Euro and token	
<b>6.0</b>	<b>Dimensions with trolley (LxWxH)</b>	1350 x 700 x 1800 mm
<b>7.0</b>	<b>Weight</b>	500 kg

# Self-Service Wash Stations

## FOS 811 FV – Liquid with pre-spraying

FRANK®



frank-hdr.de

### ► Data Sheet



<b>1.0</b>	<b>Type</b>	FOS 811 FV
<b>2.0</b>	<b>Capacity</b>	
2.1	Mains connection	400 V 3 AC 50 Hz
2.2	Nominal consumption	5,0 kW
<b>3.0</b>	<b>High pressure stage</b>	
3.1	Operating pressure max.	110 bar
3.2	Water – Volume flow	11,5 l/min
3.3	Operating temperature max.	70 °C
<b>4.0</b>	<b>Steam stage</b>	
4.2	Volume flow max.	800 l/h
4.3	Operating temperature	140 °C
4.4	Heat capacity	51 kW
4.5	Fuel oil consumption at 60 °C	4,8/5,8 kg/h - l/h
<b>5.0</b>	<b>Specification</b>	
5.1	oil-heated, 5 programmes, frost protection circuit	
5.2	HP-hose 10 m, spray gun, spray lance	
5.3	without water softener	
5.4	without boom	
5.5	with liquid detergent tank	
5.6	with oil atomization burner including pre-heater and flame control	
5.7	fuel oil tank with fuel filler and level indicator	
5.8	with electrical coin checker for 4 different coins, e.g.: 50 Cent, 1 Euro, 2 Euro and token	
<b>6.0</b>	<b>Dimensions with trolley (LxWxH)</b>	1350 x 700 x 1800 mm
<b>7.0</b>	<b>Weight</b>	500 kg

\* EU declaration of conformity updated by the TÜV Hesse

subject to change without prior notice



# Self-Service Wash Stations FOS 811 P - Powder

## ► Data Sheet



<b>1.0</b>	<b>Type</b>	FOS 811 P
<b>2.0</b>	<b>Capacity</b>	
2.1	Mains connection	400 V 3 AC 50 Hz
2.2	Nominal consumption	5,0 kW
<b>3.0</b>	<b>High pressure stage</b>	
3.1	Operating pressure max.	110 bar
3.2	Water – Volume flow	11,5 l/min
3.3	Operating temperature max.	70 °C
<b>4.0</b>	<b>Steam stage</b>	
4.2	Volume flow max.	800 l/h
4.3	Operating temperature	140 °C
4.4	Heat capacity	51 kW
4.5	Fuel oil consumption at 60 °C	4,8/5,8 kg/h - l/h
<b>5.0</b>	<b>Specification</b>	
5.1	oil-heated, 4 programmes, frost protection circuit	
5.2	HP-hose 10 m, spray gun, spray lance	
5.3	without water softener	
5.4	without boom	
5.5	with powder detergent	
5.6	with oil atomization burner including pre-heater and flame control	
5.7	fuel oil tank with fuel filler and level indicator	
5.8	with electrical coin checker for 4 different coins, e.g.: 50 Cent, 1 Euro, 2 Euro and token	
<b>6.0</b>	<b>Dimensions with trolley (LxWxH)</b>	1350 x 700 x 1800 mm
<b>7.0</b>	<b>Weight</b>	500 kg